



H.S. WHITE CORPORATION

Marine and Industrial Specialties

1350 S. Dixie Highway East • Pompano Beach, FL 33060
 Pompano (954) 785-6760 Miami (305) 940-2700 W.P.B. (561) 832-4144
 Fax (954) 785-8247 Website: www.HSWHITE.com

RED RUBBER SHEET-TYPE 95

Styrene Butadiene Rubber Sheet (Red Rubber) is a low-cost flange gasket material recommended for low temperature applications such as washers and gaskets for the heating and plumbing trades. Red Rubber is a non-oil resistant compound that resists flow under compression. It offers moderate to good performance against low pressure. Good aging and abrasion resistance and easily conforms to uneven flange faces.

The low resistance to oils makes Red Rubber better suited for general gasket applications in no-petroleum-based systems.

DURO: 75
ELONGATION: 200%
COLOR: Red-Brown

TENSILE: 400 psi
TEMP: to 180°F

Features: Plate Finish

GAUGE (inch)	WIDTH (inch)	LENGTH (ft/roll)	WEIGHT approx.. lbs/sq.yd
1/32"	36	50	2.50
1/16"	36 or 48	50	5.75
3/32"	36	50	7.75
1/8"	36 or 48	50	11.50
3/16"	36 or 48	50	17.25
1/4"	36 or 48	25	23.00