



H.S. White Corporation

Your Marine & Industrial Specialists

1350 South Dixie Highway East | Pompano Beach, FL 33060
 800-327-8575 | sales@hswhite.com | www.HSWhite.com
 Pompano Beach: 954-785-6760 | Houston: 713-589-8591

NEOPRENE SHEET—Type #90

Neoprene rubber is an all-purpose elastomer and an extremely versatile synthetic rubber used in thousands of applications. Neoprene rubber resists degradation from sun, ozone and weather and performs well in contact with oils and chemicals. Neoprene rubber maintains its strength, flexing, twisting and elongation very well over a wide temperature range while having outstanding physical toughness.

Neoprene rubber is most commonly used in bumpers, pads and sealing in general gasket and flange applications.

For uses where moderate oil and ozone resistance is required.

DURO: 50-60-70 in most sizes
TENSILE: 800 psi
TEMPERATURE: -20°F to +160°F

GAUGE: Gauge 1/32" through 1
ELONGATION: 400%
COLOR: Black

Features: Plate Finish

GAUGE (inch)	WIDTH (inch)	LENGTH (ft/roll)	WEIGHT approx. Lbs/sq.yd
1/32"	36" or 48"	50	2.75
1/16"	36" or 48"	50	4.50
3/32"	36" or 48"	50	6.80
1/8"	36" or 48"	25	9.00
3/16"	36" or 48"	25	13.50
1/4"	36" or 48"	25	18.00
3/8"	36" or 48"	25	27.00
1/2"	36" or 48"	25	36.00
3/4"	36" or 48"	25	54.00
1"	36" or 48"	25	72.00