



**H.S. WHITE
CORPORATION**

Marine and Industrial Specialists



SPIRAL WOUND GASKET SPECIFICATIONS & COLOR CHART

Windings Material - Outside Rim Color

MATERIAL	MINIMUM		MAXIMUM		ABBREVIATION	COLOR CODE
	°F	°C	°F	°C		
304 SS	-320	-195	1400	760	304	Yellow
316 SS	-150	-100	1400	760	316L	Green
321 SS	-320	-195	1400	760	321	Turquoise
347 SS	-320	-195	1700	925	347	Blue
Alloy 20 (20Cb-3)	-300	-185	1400	760	A-20	Black
Carbon Steel	-40	-40	1000	540	CRS	Silver
Hastelloy B	-300	-185	2000	1090	HAST B	Brown
Hastelloy C	-300	-185	2000	1090	HAST C	Beige
Inconel 600	-150	-100	2000	1090	INC 600	Gold
Monel	-200	-130	1500	820	MON	Orange
Nickel	-320	-195	1400	760	NI	Red
Titanium	-320	-195	2000	1090	TI	Purple

Filler Material - Rim Stripe Color

MATERIAL	MINIMUM		MAXIMUM		ABBREVIATION	COLOR CODE
	°F	°C	°F	°C		
Mica Graphite	-350	-212	1400	760	MICA-GRA	Pink
Flexible Graphite	-350	-212	950	510	F.G.	Grey
PTFE	-400	-240	500	260	PTFE	White
Ceramic	-350	-212	2000	1090	CER	Light Green