



H.S. WHITE CORPORATION

Marine Hose Solutions

Series 110/200 Marine Softwall Wet Exhaust Hose



Certified wet exhaust, heavy-wall reinforcement with multiple plies of synthetic cord. Designed for engine water circulation, heat exchanger, heavy-duty discharge lines and straight marine wet exhaust connections. Meets or exceeds USCG, ABYC, and SAE J2006 R1 standards for wet exhaust service. Recommended for short, straight connections.

Tube:	Black EPDM Blend
Reinforcement:	Multiple textile plies
Cover:	Black EPDM Blend
Temperature:	-20°F to +200°F
Branding:	Blue Mylar / White Letters

Part #	I.D. (In)	O.D. (In)	W.P. (PSIG)
110-0120	1/2	.87	169
110-0580	5/8	1.02	169
110-0340	3/4	1.14	169
110-0780	7/8	1.26	102
110-1000	1	1.36	102
100-1180	1-1/8	1.54	97
110-1140	1-1/4	1.69	97
110-1560	1-5/16	1.69	97
110-1380	1-3/8	1.81	97
200-1120	1-1/2	1.93	68
200-1580	1-5/8	2.05	68
200-1340	1-3/4	2.20	63
200-1780	1-7/8	2.32	58
200-2000	2	2.44	58
200-2140	2-1/4	2.68	58
200-2380	2-3/8	2.80	87

Part #	I.D. (In)	O.D. (In)	W.P. (PSIG)
200-2120	2-1/2	2.91	87
200-2580	2-5/8	3.03	87
200-2780	2-7/8	3.27	77
200-3000	3	3.46	77
200-3184	3-1/8	3.58	73
200-3124	3-1/2	3.98	63
200-3344	3-3/4	4.17	63
200-4004	4	4.45	58
200-4184	4-1/8	4.57	58
200-4124	4-1/2	4.92	63
200-5004	5	5.55	77
200-5124	5-1/2	6.06	68
200-6004	6	6.69	58
200-6584	6-5/8	7.32	58
200-8004	8	8.74	48

Contact Us



1.800.327.8575



HSWhite.com